



SUNTRONIC

Outdoor LCD Signage

Model: U4600L

46" Large Screen Digital Signage Monitor
High Bright LED Enhanced Sunlight Readable
Display

SPECIFICATIONS:

LCD panel	46" TFT-LCD
Display Size	1018.353 x 572.544 mm ² , 46inch
Resolution	1920 x 1080 RGB
Pixel Pitch	0.5302 x 0.5302 mm
Color	16.7 M
Horizontal Freq.	62.13KHz ~ 75.6KHz
Vertical Freq.	57Hz ~ 63Hz
Brightness	1100 cd/m ² , LED backlight enhanced
Contrast	2000 : 1
Dimming	Auto dimming by light sensor
Viewin Angle	89/89/89/89
Response Time	15ms / 5ms
Interface	VGA, AV, S-video, HDMI (round connector IP66)
Video System	PAL/SECAM/NTSC-3.58, NTSC-4.43, PAL-60
Remote control	Support for full OSD features
Operate Voltage	AC 100 ~ 240V 60/50Hz
Power Consumption	750 Watt for monitor, Additional 120 Watt for optional Heater
Stand by mode	25 W or less
Enclosure	IP54
Protection	4-6mm Vandal glass at the front
Accessories	AC Power Cord, Remote Control. VGA cable x 1, S-Video cable x 1, HDMI Cable x1
Environmental	Operating temperature 5F ~ 110F, (Optional add heater reach to -22F) Operating Humidity 10% ~ 85% Storage temperature -20 ~ 60C Storage Humidity 5% ~ 95%