



SUNTRONIC

Outdoor LCD Signage

Model: U5200L

52" LCD Signage Monitor with
High Bright LED Enhanced Direct Type Backlight

SPECIFICATIONS:

| | |
|--------------------------|--|
| LCD panel | a-Si TFT active matrix |
| Display Size | 1152 x 648 mm, (52.037 inch) |
| Resolution | 1920 x RGB x 1080 |
| Pixel Pitch | 0.2 (H) x 0.2 (V) mm |
| Color | 16.7 M |
| Horizontal Freq. | 60KHz ~ 80KHz |
| Vertical Freq. | 50Hz /60Hz frame rate |
| Brightness | 1100 cd/m² , LED Array backlight enhanced |
| Contrast | 1500 : 1 Dynamic contrast ratio: 10000:1 |
| Dimming | Auto dimming by light sensor |
| Viewin Angle | 88/88/88/88 |
| Color Gamut | 72% NTSC |
| Response Time | 6.5ms |
| Interface | VGA (round connector IP66), DVI or HDMI |
| Video System | PAL/SECAM/NTSC-3.58, NTSC-4.43, PAL-60 |
| Video In | S-Video (round connector IP66) |
| Remote control | Support for full OSD features |
| Operate Voltage | AC 100 ~ 240V 60/50Hz |
| Power Consumption | 750 Watt for complete monitor, additional 160 Watt for optional Heater |
| Stand by mode | 15 W or less |
| Enclosure | IP54 Stainless Steel Enclosures |
| Protection | 4--6mm Vandal glass on the front |
| Accessories | AC Power Cord, IR Remote Control VGA cable x 1, S-Video cable x 1 |
| Environmental | Operating Temperature -10 ~ 50C (Optional add heater reach to -22F) Operating Humidity 10% ~ 85% Storage temperature -20 ~ 60C Storage Humidity 5% ~ 95% |

Model: U5200L

52" LCD Signage Monitor with High Bright LED Enhanced Direct Type Backlight

MECHANICAL DRAWING:

