



SUNTRONIC

Outdoor LCD Signage

Model: U5500L

55" LCD Signage Monitor with
High Bright LED Enhanced Direct Type Backlight

SPECIFICATIONS:

LCD panel	55" TFT-LCD
Display Size	1209.60(H) x 680.40(V) (54.6" diagonal)
Resolution	1920 x 1080 RGB
Pixel Pitch	0.21(H) x 0.63(V)
Color	16.7 M
Horizontal Freq.	60KHz ~ 80KHz
Vertical Freq.	50Hz /60Hz frame rate
Brightness	1200 nits, LED Array backlight enhanced
High Contrast	1800 : 1 Dynamic contrast ratio: 7200:1
Dimming	Auto dimming by light sensor
Viewing Angle	88/88/88/88
Color Gamut	72% NTSC
Response Time	6.5ms
Interface	VGA (round connector IP66), DVI or HDMI
Video System	PAL/SECAM/NTSC-3.58, NTSC-4.43, PAL-60 (reserved for internal media player) media player with Ethernet and WiFi (option) S-Video (round connector IP66)
Media player	Support for full OSD features
Video In	AC 100 ~ 240V 60/50Hz
Remote control	912 Watt for complete monitor
Operate Voltage	25 W or less
Power Consumption	Alu block milled front, Alu sheet folded backcover, IP65
Stand by mode	4--6mm Vandal glass at the front
Enclosure	AC Power Cord, Remote Control.
Protection	VGA cable x 1, S-Video cable x 1
Accessories	Operating temperature -10 ~ 45C
Environmental	Operating Humidity 10% ~ 85%
	Storage temperature -20 ~ 60C
	Storage Humidity 5% ~ 95%