

# 70" Outdoor LCD GS7000L



SuntronicLCD's All-Weather/outdoor Full Sun environment Sunlight Readable LCD monitors allow you to view the display under the full sunlight. These affordable solutions are ready to deploy to any indoor and outdoor digital signage application for retail stores, restaurants, gas stations and many more...

We produce the largest and brightest Sunlight Readable LCD Monitor in sizes from 32" to 82"

## Features Highlight:

- High-Brightness LCD Panel
- All Weather Proof IP65 Enclosures
- Operating Temperature -40C To 50C\*
- Integrated heater and air conditioner
- Vandal Resistant Screen & housing
- Unique Front Access Design
- Remote Reboot/Temp.& Humidity Monitoring available (Optional)
- Wireless and VGA/DVI CAT5 signal extenders available (Optional)

## Technical Specifications

Active area size (W x H)	70" (1549.44 x 871.56 mm)
Pixel pitch (mm)	0.807(H) x 0.807(V)
Panel resolution (pixels)	1920 x 1080
Luminance of white (Brightness)	2000 nits (Typ)
Contrast ratio	2500:1
Response time (gtg)	8 ms (Typ)
Colour Range	16.7 Million colours (max)
Viewing angle	89/89/89/89
Video inputs	VGA; DVI; S-Video
Auto Brightness Control	Yes (Optional)
Front glass type	Strengthen 10mm AR glass
IP Class	IP65
Operating temperature range Area)	-40 to + 100F (Direct Sunlight) /110F (Under Shaded
Storage Temperature	0 to 50C
CCFL Life Time	60K hrs (min)
Input voltage	110V
Weight	550lbs
External dimensions (W x H x D) proper	1830W x 1152H x TBD mm Notes: to guarantee a
Portrait version	functionality, 10cm of clearance must be
Available Accessories	kept around the display
Options	GS7000P, please contact I-Tech for details
Customization	IR Remote Control
	Custom Embedded PCs (please call for enquiries)
	Please contact SuntronicLCD for available options

