

All Weather Outdoor LCD

Suntronic's GS4600HDL installed at FAST Transit, Fairfield Station USA



- ▶ **Brightness: 1500 nits**
- ▶ **All Weather Proof IP65 Enclosures**
- ▶ **Operating Temperature -40C To 50C***
- ▶ **Integrated heater and air conditioner**
- ▶ **Slim Bezel Thickness 30mm only**
- ▶ **High-Brightness LCD Panel**

Suntronic's GS4600HDL installed at Fast Transit, Fairfield Station, USA

Suntronic's All-Weather/Outdoor Full-Sun environment Sunlight Readable LCD monitors that allow you to view the display under the full sunlight. These affordable solutions are ready to deploy to any indoor and outdoor digital signage application for retails stores, restaurants, gas stations and many more...

Photos:



Features Highlight:

- High-Brightness LCD Panel
- All Weather Proof IP65 Enclosures
- Operating Temperature -40C To 50C*
- Integrated heater and air conditioner
- Slim Bezel Thickness 30mm only
- Vandal Resistant Screen & housing
- Unique Front Access Design
- Remote Reboot/Temp.& Humidity Monitoring available (Optional)
- Wireless and VGA/DVI CAT5 signal extenders available (Optional)

Technical Specifications:

Active area size (W x H): 46" (1018.353 x 572.544 mm)

Pixel pitch (mm): 0.2485(H) x 0.7455(V)

Panel resolution (pixels): 1366 x 768

Luminance of white (Brightness): 1500 nits (Typ)

Contrast ratio: 3000:1

Response time (gtg): 8 ms (Typ)

Colour Range: 16.7 Million colours (max)

Viewing angle: 89/89/89/89

Video inputs: VGA; HDMI; S-Video

Auto Brightness Control: Yes (Optional)

Front glass type: strengthen 6mm AR glass

IP Class: IP65

Operating temperature range: -40 to + 95F (Direct Sunlight) /122F (Under Shaded Area)

Storage Temperature: 0 to 50C

CCFL Life: Time 60K hrs (min)

Input voltage: 110V

Weight: 70kg/195lbs

External dimensions (W x H x D): 1056 x 610 x 249 mm Notes: to guarantee a proper functionality, 10cm of clearance must be kept around the display (41.6" W x 24" H x 9.81"D)

Portrait version: Please contact SuntronicLCD for details

Available Accessories: IR Remote Control VGA cable (included) and Ethernet Cable (not included)

Options: Custom Embedded PCs (please call for enquiries)

Customization: Please contact SuntronicLCD for available options