



Product Highlights:


- ▶ **Brightness: 1700 nits**
- ▶ **All Weather Proof IP65 Enclosures**
- ▶ **Operating Temperature -40C To 50C***
- ▶ **Integrated heater and air conditioner**
- ▶ **High-Brightness LCD Panel**

Suntronic's GS5500L New Launched in FLORIDA, Ransom Everglades School

Suntronic's All-Weather/Outdoor Full-Sun environment Sunlight Readable LCD monitors that allow you to view the display under the full sunlight. These affordable solutions are ready to deploy to any indoor and outdoor digital signage application for retails stores, restaurants, gas stations and many more...



Photos



Features Highlight:

- High-Brightness LCD Panel
- All Weather Proof IP65 Enclosures
- Operating Temperature -40C To 50C*
- Integrated heater and air conditioner
- Vandal Resistant Screen & housing
- Unique Front Access Design
- Remote Reboot/Temp.& Humidity Monitoring available (Optional)
- Wireless and VGA/DVI CAT5 signal extenders available (Optional)

Technical Specifications:

Active area size 55" (1387.80mm) diagonal

Outline Dimension 1286.0(H) x 745.0(V) x 60(D) mm (Typ.)

Pixel format (pixels) 1920(H) x 1080(V) (RGB stripes arrangement)

Color depth 10-bit , 1.07Billion colors

Luminance of white (Brightness) 1700 nits (Typ) at center 1 point

Contrast ratio 1600:1

Response time (gtg): 8 ms (Typ)

Colour Range: 16.7 Million colours (max)

Viewing angle: 89/89/89/89

Video inputs: VGA; HDMI; S-Video

Auto Brightness Control: Yes (Optional)

Front glass type: strengthen 6mm AR glass

IP Class: IP65

Operating temperature range: -40 to + 95F (Direct Sunlight) / 122F (Under Shaded Area)

Storage Temperature: 0 to 50C

CCFL Life Time 60K hrs (min)

Input voltage 110V

Weight 350lbs

External dimensions (W x H x D)

1470 x 906 x 463 mm (58" x 35.7" x 18.2")

Customization: Please contact SuntronicLCD for available options