

Suntronic's Outdoor LCD Display

GS Series 55" LCD GS5500L1 Installed at Recognition Plaza IOWA



Product Highlights:

- ▶ **Brightness: 1200 nits**
- ▶ **All Weather Proof IP65 Enclosures**
- ▶ **Operating Temperature -40C To 50C***
- ▶ **Integrated heater and air conditioner**
- ▶ **Vandal Resistant Screen & housing**
- ▶ **High-Brightness LCD Panel**

Suntronic's GS5500L1 New Launched in Recognition Plaza IOWA

Suntronic's All-Weather/Outdoor Full-Sun environment Sunlight Readable LCD monitors that allow you to view the display under the full sunlight. These affordable solutions are ready to deploy to any indoor and outdoor digital signage application for retail stores, restaurants, gas stations and many more...



Photos



Features Highlight:

- High-Brightness LCD Panel
- All Weather Proof IP65 Enclosures
- Operating Temperature -40C To 50C*
- Integrated heater and air conditioner
- Vandal Resistant Screen & housing
- Unique Front Access Design
- Remote Reboot/Temp.& Humidity Monitoring available (Optional)
- Wireless and VGA/DVI CAT5 signal extenders available (Optional)

Technical Specifications:

Active area size 55" (1387.80mm) diagonal
Outline Dimension 1286.0(H) x 745.0(V) x 60(D) mm (Typ.)
Pixel format (pixels) 1920(H) x 1080(V) (RGB stripes arrangement)
Color depth 10-bit , 1.07Billion colors
Luminance of white (Brightness) 1200 nits (Typ) at center 1 point
Contrast ratio 1600:1
Response time (gtg) 8 ms (Typ)
Colour Range 16.7 Million colours (max)
Viewing angle 89/89/89/89
Video inputs VGA; HDMI; S-Video
Auto Brightness Control Yes (Optional)
Front glass type Strengthen 6mm AR glass
IP Class IP65
Operating temperature range -40 to + 95F (Direct Sunlight) /122F (Under Shaded Area)
Storage Temperature 0 to 50C
CCFL Life Time 60K hrs (min)
Input voltage 110V
Weight 350lbs
External dimensions (W x H x D)
1470 x 906 x 463 mm (58" x 35.7" x 18.2")
Customization: Please contact SuntronicLCD for available options