Product Highlights:

- Brightness: 1500
- All Weather Proof IP65 Enclosures
- Operating
 Temperature
 -4°F to + 120°F
- Integrated heater and air conditioner
- Powder Coated Finish

SL/SP: All Weather proof SunTronic's SL/SP Line Digital Outdoor Signage provide a completely Sealed NEMA4/IP65 with moisture proofing and dust protection Standalone LCD Pedestal/Stand.

Our Unique Active cooling system is designed to allow the digital LCD screen to be placed in cold and warm environments from -40F up to 120F*, even in direct sunlight. Industrial Grade DID LCD Super High brightness from 1200nits to 3000nits and High Contrast. Options for integrated PC, Touchscreen and Video Extenders.

Photos:









Outdoor LCD Signage

Features Highlight:

- High-Brightness LCD Panel
- All Weather Proof IP65 Enclosures
- Operating Temperature -40C To 50C*
- Integrated heater and air conditioner
- Slim Bezel Thickness 30mm only
- Air conditioning & Heater
- Powder Coated Finish
- IP65/NEMA4X Vandal Resistant Enclosures
- Flexible Mounting Options

Technical Specifications:

Active area size (WxH) (1018.4×572.5) Panel resolution (pixels) 1920×1080

Luminance of white (Brightness) 1500 nits (Typ)

Contrast ratio 3000:1

Response time (gtg) 8 ms (Typ)

Viewing angle 89/89/89/89

Video inputs VGA+HDMI

Auto Brightness Control Yes (Optional)

Front glass type AR Safety 6mm glass

IP Class IP65/NAMA 4 Enclosures

Operating temperature range -4°F to + 120°F

Storage Temperature 0 to 50C Input voltage 110V

Weight 70kg/195lbs

External dimensions (W x H x D) 1056 W x 610 H x 249 D mm

Available Accessories

Integrated PC, Touchscreen, Integrated CAT5/Fiber Optics VGA/DVI Extenders, Custom Embedded PCs and Wireless, Serial RS232 Input, Screen Sensor/Environmental Sensors, Auto

Brightness Control Sensor, IR Remote Control and VGA cable (included)and Ethernet Cable (not included)