

W4600HDL1

Store Front Window High Brightness LCD
for advertising and Dynamic Food Menu

Installed at 1228 Galleria Blvd Ste 130 Roseville, CA 95678

SUNTRONIC
Outdoor LCD Signage

Product Highlights:

- ▶ **Brightness: 1500 nits**
- ▶ **Perfect Application for Behind window displays**
- ▶ **Aspect Ration: 16:9**
- ▶ **Completely Sunlight Viewable**
- ▶ **1920 x 1080 Max. Resolution**
- ▶ **Digital or Analog Interface**

SunTronic's W Series is designed to use it behind window display includes Stainless steel enclosures and latest LED highbrightness technology brightness up to 1500nits. Application for Banks, retail store, Real Estate store front and more...



Features Highlight:

- Perfect Application for Behind window displays
- 1500nits Bright Active Matrix TFT-LCD Display
- Stainless Steel Enclosures (Optional)
- 1920 x 1080 Max. Resolution
- Digital or Analog Interface
- Wide Viewing Angles 178 deg (L/R)
- Auto Dimming
- Aspect Ration: 16:9
- Completely Sunlight Viewable

Technical Specifications:

Active area size (W x H): 46"

Panel Type: TFT Active

Resolution Capabilities: 1920 x 1080, VGA to WUXGA

Pixel Pitch: 0.53(H) x 053(V) mm

Viewing Angle: Left / Right: 89°/89° Up / Down: 89°/89°

Active Area: 1018.08(H) x 572.67 (V) mm

Contrast Ratio: Dynamic contrast ratio: 5000:1

Brightness: 1500 nits, Completely Sunlight Viewable

Backlight: 50,000 Hours Typical

Colors Supported: 16.7 M

Video Input: VGA, DVI and HDMI

Power Source: 90-260 VAC

Power Consumption: 90 Watts, for complete monitor at full brightness, <2 Watts Sleep Mode

Temperature: Operating: -0° to 50°F

Storage: -20° to 60°C

Humidity Operating: 10 to 90% NC

Storage: 10 to 90% NC

Response Time: 8msec typical (G-to-G)

Dimensions With Flanges(W x H x D): TBD

Without Flanges(W x H x D): 1122.0 x 666.0 x 136.0 (mm)

Weight (Without Stand)

38.0 Kgs/41.0 Kgs

Warranty: 1 year